



# SPLIT TYPE AIR CONDITIONING UNITS

## Evaporator Unit



### 9,000

Gross Dimensions: 870mm x 350mm x 265mm  
Net Dimensions: 800mm x 270mm x 180mm

### 12,000

Gross Dimensions: 870mm x 350mm x 265mm  
Net Dimensions: 800mm x 270mm x 180mm

### 18,000

Gross Dimensions: 1010mm x 350mm x 265mm  
Net Dimensions: 1000mm x 320mm x 210mm

### 24,000

Gross Dimensions: 1190mm x 380mm x 300mm  
Net Dimensions: 1000mm x 320mm x 210mm

### 36,000

Gross Dimensions: 1345mm x 430mm x 335mm  
Net Dimensions: 1250mm x 325mm x 230mm



## Condenser Unit

9,000 Gross Dimensions: 790mm x 340mm x 485mm Net Dimensions: 800mm x 260mm x 550mm  
12,000 Gross Dimensions: 825mm x 320mm x 550mm Net Dimensions: 800mm x 260mm x 550mm  
18,000 Gross Dimensions: 920mm x 335mm x 595mm Net Dimensions: 860mm x 300mm x 610mm  
24,000 Gross Dimensions: 995mm x 415mm x 690mm Net Dimensions: 880mm x 360mm x 650mm  
36,000 Gross Dimensions: 1045mm x 930mm x 335mm Net Dimensions: 895mm x 860mm x 330mm



**Mitsubishi compressor**

**5 year Factory warranty**

## R22 Series

## Technical parameters for Mini Split 50Hz

Model	Reference #	Rated volt	Rated frequency (Hz)	Rated Cooling Capacity (BTU/H)	Rated Heating Capacity (BTU/H)	Rated Cooling Power Consumption (W)	Rated Heating Power Consumption (W)	Rated Cooling Current Input (A)	Rated Heating Current Input (A)	Maximum Power Consumption (W)	Maximum Current Input (A)	Indoor /Outdoor Noise	Indoor Discharge Airflow (CFM)	Pipe Size (inch)	Indoor Unit Weight (kg)	Outdoor Unit Weight (kg)	Energy Efficiency Rating (EER)	Coefficient of Performance (COP)
9,000	KFR-25GW	220	50	8530	9554	860	800	4.0	3.7	1200	6.5	34~42/55	253	1/4+3/8	10.5	30	2.63	3.3
12,000	KFR-32GW	220	50	11520	11601	1250	1180	5.8	5.4	1630	8.8	35~42/58	277	1/4+1/2	11	35	2.9	3.2
18,000	KFR-51GW	220	50	17401	19142	1890	1700	8.9	8.0	2500	13.1	40~46/54	500	1/4+1/2	13	40	2.7	2.9
24,000	KFR-66GW	220	50	22520	26273	2785	3010	12.8	13.8	3810	20.7	45~50/62	462	3/8+5/8	19	50	2.65	2.9
36,000	KFR-88GW	220	50	35000	38000	4120	4100	18.6	18.5	4500	25.7	42~49/59	1350	3/8+5/8	18	82	2.49	2.72